## IN THE CLAIMS:

Claim 19 is amended herein. Claims 21 and 22 are canceled without prejudice. Claims 35 and 36 are added herein. All pending claims and their present status are produced below.

1. (Previously presented) A system of detecting radio frequency interference and correcting damaged composite video data signal, comprising:

a detection unit for receiving a composite video signal to detect whether interference causes damage to the received composite video data signal and, for identifying a damaged portion of the received composite video data signal; and

a correction unit, communicatively coupled with the detection unit, for correcting the damaged portion of the composite video data signal in response to identification of the damaged portion of the composite video data signal by replacing the damaged portion of the composite video signal with an equivalent portion of video data corresponding to the damaged portion of the composite video signal.

2. (Original) The system of claim 1, further comprising:

a transmission end for generating the composite video signal and transmitting the composite video signal to the detection unit.

3. (Original) The system of claim 2, wherein the transmission end comprises:

a video sensor for capturing video image;

an encoder, coupled to the video sensor, for converting captured video image into the composite video data signal; and

a transmitter, coupled to the encoder, for transmitting composite video data signal to the detection unit.

4. (Original) The system of claim 3, wherein the transmission end further comprises: a microphone for recording audio signal and for transmitting audio signal to the transmitter.

5. (Original) The system of claim 3, wherein the composite video data signal is a NTSC compliant video signal.

6. (Original) The apparatus of claim 3, wherein the composite video data signal is a PAL compliant video signal.

7. (Canceled).

8. (Canceled).

9. (Canceled).

10. (Canceled).

11. (Canceled).

12. (Canceled).

13. (Canceled).

14. (Canceled).

15. (Canceled).

16. (Canceled).

17. (Canceled).

18. (Canceled).

19. (Currently amended) A method of detecting external interference within a composite video signal representing a line on a video image, comprising the steps of:

receiving the composite video signal;

detecting whether a color burst pulse is damaged in the composite video signal;

generating a detection flag in response to the condition of the color burst in the composite video signal; and

replacing, in response to the detection flag, the color burst pulse that is damaged with an equivalent pulse corresponding to the damaged color burst pulse.

20. (Original) The method of claim 19, further comprising:

detecting whether a horizontal synchronization pulse is damaged in the composite video signal.

21. (Canceled)

22. (Canceled)

23. (Previously presented) A system of detecting radio frequency interference and correcting a damaged composite video data signal, comprising:

a detection unit for receiving a composite video signal, detecting whether interference causes damage to the received composite video data signal, and identifying a damaged portion of the received composite video data signal; and

a correction unit, communicatively coupled with the detection unit, for identifying the damaged portion of the composite video data signal for correction,

wherein the detection unit further comprises:

a receiver module for receiving the composite video data signal,

a bad-line detector, coupled to the receiver module, for determining if the composite video data signal is damaged by detecting whether a predetermined portion of the composite video data signal is present and, in response to detecting damage, generating a detection flag to indicate the damaged video data signal,

a video decoder, coupled to the receiver module, for converting the composite video data signal into component video data signal, and

a line flattener, coupled to the video decoder and the bad-line detector, for receiving the detection flag and modifying a corresponding damaged portion of component video data to a predetermined value.

24. (Previously presented) The system of claim 23, further comprising a mute control module, coupled to the receiver module and the bad-line detector, for muting audio signals associated with damaged portion of composite video signal in response to receiving the detection flag from the bad-line detector.

25. (Previously presented) The system of claim 23, further comprising a video compressor, coupled to the line flattener, for compressing the component video data and transmitting to the correction unit.

26. (Previously presented) The system of claim 23, wherein the bad-line detector further comprises:

a filter for receiving the composite video data signal from the receiver module and for outputting the color burst signal of the composite video data signal;

a color burst processing module, coupled to the filter, for amplifying and converting the color burst signal into a color burst square wave;

a synchronization detector, coupled to the receiver module, for detecting and outputting a horizontal synchronization signal in the composite video data signal; and

a logic unit, coupled to the color burst processing module and the synchronization detector, for detecting if the color burst signal and the horizontal synchronization signal have been damaged by interference and for generating the detection flag in response to determination of the damage caused by interference.

27. (Previously presented) The system of claim 26, wherein the logic unit is further configured to count a number of color burst edges in the color burst square wave.

28. (Previously presented) The system of claim 26, wherein the logic unit is further configured to detect if the horizontal synchronization signal of each composite video line has a rising edge at a first predetermined time.

29. (Previously presented) The system of claim 26, wherein the logic unit is further configured to detect if the horizontal synchronization signal of each composite video line has a falling edge at a second predetermined time.

30. (Previously presented) The system of claim 26, wherein the detection flag is a bad-line flag.

31. (Previously presented) A system of detecting radio frequency interference and correcting a damaged composite video data signal, comprising:

a detection unit for receiving a composite video signal, detecting whether interference causes damage to the received composite video data signal, and identifying a damaged portion of the received composite video data signal; and

a correction unit, communicatively coupled with the detection unit, for identifying the damaged portion of the composite video data signal for correction,

wherein the correction unit further comprises:

a video decompressor, coupled to the detection unit, for storing video data corresponding to the composite video data signal and for decompressing the stored video data wherein the stored video data correspond to video frames,

a bad-line logic, coupled to the video compressor, for identifying the damaged portion in the stored video data, the damaged portion being detected and marked by the detection unit, and

a bad-line replacement module, coupled to the video decompressor and the bad-line logic, for replacing damaged portion in the stored video data with good video data.

32. (Previously presented) The system of claim 31, further comprising:

an audio stream assembly, coupled to the detection unit, for transferring audio signals in the composite video data signal;

an audio delay module, coupled to the audio stream assembly, for delaying audio signals; and

an audio driver backend, coupled to the audio delay module, for transferring delayed audio signals to an audio processing module.

33. (Previously presented) The system of claim 31, further comprising a video driver backend, coupled to the bad-line replacement module, for transferring repaired video data to a video application processing module.

34. (Previously presented) The system of claim 31, wherein the bad-line replacement module comprises:

a plurality of buffers for storing the video data;

an input multiplexer, coupled to each of the plurality of buffers, for receiving the video data and selecting one of the plurality of the buffers to store video data corresponding to one video frame; and

an output multiplexer, coupled to each of the plurality of buffers, for selecting one of the plurality of the buffers to output video data corresponding to one video frame.

35. (New) A computer readable medium configured to store instructions executable by a processor, the instructions structured for:

detecting whether a color burst pulse is damaged in the composite video signal;

generating a detection flag in response to the condition of the color burst in the composite video signal; and

replacing, in response to the detection flag, the color burst pulse that is damaged with an equivalent pulse corresponding to the damaged color burst pulse.

36. (New) The computer readable medium of claim 35, wherein the instructions are further structured for detecting whether a horizontal synchronization pulse is damaged in the composite video signal.